



Flight Light Inc.  
2708 47th Ave.  
Sacramento, California, U.S.A.  
95822-3806



**ALSF-II System**  
**240/480V ac**  
**Honeywell**

PH (916) 394-2800    FX (916) 394-2809  
TF (800) 806-3548    EM info@flightlight.com

## ALSF-II System

Model: GEA20-0207-2, Three Intensity with Lamp Monitoring:  
Category II or III Weather Conditions, 240/480 V ac

The Honeywell Approach Lighting System with Sequence Flashing Lights (ASL-II) is a high intensity approach lighting system that provides a visual lighting path for landing the aircraft.


The ALSF-II system usually is a 3000-foot-long array of lights but can be longer or shorter depending on local terrain and requirements.

A typical ALSF-II system consist of the following light fixture components:

- 30 light bars each with 5 steady burning white PAR56 fixtures
- 2 light bars each with 8 steady burning white PAR56 fixtures
- 2 light bars each with 4 steady burning white PAR56 fixtures
- 18 light bars each with 3 steady burning red PAR56 fixtures
- 21 sequence flashing white PAR56 fixtures
- Threshold bar of 49 steady burning green PAR56 fixtures.

The ALSF-II system can be mounted on 2-inch EMT, up to a 6-foot mounting height or on frangible towers over 6 feet. The system includes lamp monitoring as a standard feature.

System control of the sequence flashing lights is accomplished through the master controller selecting one of three light intensities: low, medium, or high. The steady burning white and red PAR56 fixtures are controlled by separate circuits connected to constant current regulators located in the airport lighting vault. Both the sequence flashing and the steady burning light systems provide for either local or remote control.



Typical ALSF-II Layout

Visit our web site: [www.flightlight.com](http://www.flightlight.com)



Flight Light Inc.  
2708 47th Ave.  
Sacramento, California, U.S.A.  
95822-3806



**ALSF-II System**  
**240/480V ac**  
**Honeywell**

PH (916) 394-2800    FX (916) 394-2809  
TF (800) 806-3548    EM info@flightlight.com

**ALSF-II System Components - GEA20-0207-2**

**ALSF-II System Specification - GEA20-0207-2**

System Components	Qty	Part Number	Weight (lb)
<b>SEQUENCE FLASHING LIGHTS:</b>			
Control cabinet, 240/480 V	1	GEA20221-1	80.0
Power supply, 240/480 V	21	GEA20540A-1M	80.0
Flash head	21	GEA20360	4.0
Cable assembly, 60 ft	21	GEA20151-1	5.0
Junction box	21	GEA20169	7.0
Frangible coupling	86	75-59E	1.0
Flanges:			
- Floor	86	B1A00093DE3	1.0
- Base	44	GEA20316-1	0.5
Aiming device	1	GEA80008	0.5
Flasher tester, 120 V	1	GEA20362-2	3.0
Manual, 120/240 V	1	BFG-M20-211	-
<b>STEADY BURNING FIXTURES:</b>			
PAR56 fixture	277	GEA80	3.0
Filters:			
- Red	62	AP3510R	2.0
- Green	49	AP3510G	2.0
Frangible coupling	277	40000163-001	1.0
Cord set 6 ft	277	GEA20152-18	1.0
Shorting device (optional)	277	GE80030	1.0
Lamps:			
- 300 W, 20 A	215	Q20A/PAR56/C	1.0
- 500 W, 20 A	62	Q20A/PAR56/1	1.0
Transformer:			
- 300 W, 20/20 A	215	L-830-9	21.0
- 500 W, 20/20 A	62	L-830-13	22.0
Primary connector kits	277	L-823	1.0

<b>OPERATIONAL:</b>		
Sequence flashing lights	Input power	240/480 V ac, 60 Hz; single-phase, 3-wire center tap
	Current	30 A ac
	Power	7.2 k Va
Steady burning lights	Input power	5,000 V ac, 60 Hz
	Current	20 A
	Power	79.2 kW
<b>ENVIRONMENT:</b>		
	Temperature	-55 to +55°C
	Relative humidity	0 to 95%
	Altitude	10,000 ft
<b>PHOTOMETRIC:</b>		
	High intensity	8,000 to 20,000 candela
	Medium intensity	800 to 2,000 candela
	Low intensity	150 to 450 candela
<b>EQUIPMENT:</b>		
Sequence flashing FFA-E-2628		
<b>APPLICATIONS:</b>		
Category II Standard or Category II Conditional		

**ALSF-II System Components - GEA20-0207-2**

System Components	Qty	Part Number	Weight (lb)
Spare parts trunk	1	GEA20041	-
Transformer bases with cover	277	L-867B	-
Frangible tower assemblies	1 Lot	--	-

Visit our web site: [www.flightlight.com](http://www.flightlight.com)