



Flight Light Inc.
2708 47th Ave.
Sacramento, California, U.S.A.
95822-3806

PH (916) 394-2800 FX (916) 394-2809
TF (800) 806-3548 EM info@flightlight.com

PAR56/PAR38
Elevated Approach Lights
Type: 982H
Honeywell

PAR56/PAR38 Elevated Approach Lights

Type: 982H

USE

Honeywell Elevated Approach Lights are designed for use for all FAA Approach Lighting Systems. The PAR 56 Light is commonly used in High Intensity Approach Lighting Systems (ALSF, SSALR) as well as on the Medium Intensity Approach Lighting System Threshold (MALSR Threshold). The PAR 38 light used exclusively in medium intensity system centerline and wing bar lights. Both lights can be mounted in many different ways, including frangible couplings, EMT, or LIR Crossbars.

FEATURES

- Fixtures can mount on frangible coupling or approach masts, depending on the application.
- Lamps are available in constant current and constant voltage inputs in many different wattages.
- No tools required to re-lamp
- Aiming device (optional) allows for easy, accurate, vertical alignment.
- 2-piece casting; minimal parts.



Visit our web site: www.flightlight.com



Flight Light Inc.
 2708 47th Ave.
 Sacramento, California, U.S.A.
 95822-3806

PH (916) 394-2800 FX (916) 394-2809
TF (800) 806-3548 EM info@flightlight.com

PAR56/PAR38
Elevated Approach Lights
Type: 982H
Honeywell

Elevated Approach Light Spare Parts and Accessories

Part Number	Description
GEA20117	PAR38 Aiming Device
10045	PAR38 Lamp Socket
GEA20459-3	PAR38 Head Casting
GEA20459-4	PAR38 Slipfitter
40000163-001	Frangible Coupling
B1A0009SDE3	Floor Flange
GEA20152-18	Cable Assembly, 6 ft
ET20066601	200W, 6.6/6.6A Isolation Transformer
ET30062601	300W, 6.6/20A Isolation Transformer
ET30022601	300W, 20/20A Isolation Transformer
ET50022601	500W, 20/20A Isolation Transformer
GEA80008	PAR56 Aiming Device
XLGB3LS0C	PAR38 Lamp Socket (plug-in)
GEA80034	PAR56 Head Casting
GEA80039-1	PAR56 Slipfitter
GE80030	PAR56 Shorting Device
GEA80009	PAR56 Lamp Clip
GEA80007	PAR56 Filter Clip
EK54D3D3	Primary Connector Kit No. 6
EK54D4D4	Primary Connector Kit No. 8
EK90RA6	Secondary Receptacle No. 12
EK90PA6	Secondary Plug No.12

Elevated Approach Light Part Numbers

Part No	Description
Lamp Holders	
GEA80	PAR56 Lamp Holder
GEA20074-1	PAR38 Lamp Holder
Lamps	
100PAR/SF	PAR38, 100 W, 120 V ac Spot
120PAR/FLWM	PAR38, 120 W, 120 V ac Wide
150PAR/SF	PAR38, 150 W, 120 V ac Spot
150PAR/WFL	PAR38, 150 W, 120 V ac Wide
300PAR56/NSP	PAR56, 300 W, 120 V ac
Q500PAR56/NSP	PAR56, 500 W, 120 V ac
Q6.6A/PAR562	PAR56, 200 W, 6.6A
Q20A/PAR56IC	PAR56, 300 W, 20A
Q20A/PAR56/1	PAR56, 500 W, 20A
Color Filters (PAR56 Only)	
AP3510G	PAR56 Green
AP3510R	PAR56 Red

Elevated Approach Light Dimensions and Shipping Information

Dimensions	Shipping
PAR56 Fixture	
Size: 9.5 in. x 8 in. x 6.5 in. (typical)	Shipping Volume: 0.35 cu ft
Weight: 2.25 lbs.	Shipping Weight: 3 lbs
PAR38 Fixture	
Size: 7 in. x 3 in. x 6 in. (typical)	Shipping Volume: 0.35 cu ft
Weight: 1.25 lbs	Shipping Weight: 2 lbs

Visit our web site: www.flightlight.com